# Protean<sup>™</sup> HT Radio Remote Control

# Protean<sup>™</sup> HT Transmitter



P.N. 701PROL6B-TX

## **Transmitter Specifications**

up to 330 feet and is available for either AC or DC operation.

• Dimensions: 6.5H x 2.0W x 2.25D (165mm x 51mm x 57mm)

The Protean<sup>™</sup> HT Radio Remote Control is ideal for controlling hoist and trolley operation. It features two-speed push buttons with distinct position detents. There is a large mushroom E-stop switch with removable water-proof key. The radio functions in a range

- 4 Buttons: Up, Down, East, West
- Uses 2 AA alkaline batteries
- Shock-resistant design

# Protean<sup>™</sup> Receiver



#### Please Note:

All transmitters will require the Serial Number for proper matching to receiver for programming.

Protean Series radios will also need Channel Number 0-45 specified at time of order.

#### **Receiver Specifications**

- Dimensions: 6.5H x 3.0W x 2.4D (165mm x 76mm x 60mm)
- NEMA 4 rated (IP65), shock resistant enclosure
- Pre wired with six feet (1.83M) of cable
- Shock-resistant mounting; four bolts with stock absorbers
- Power Options: DC Type: 12 ~ 24 Volts DC (or 24 Volts AC) AC Type: 48/110, 110/220, plus or minus 10%, 50/60 Hz. Default is 48/110 VAC, 110 VAC selected
- Relay Ratings: 10A @ 125 VAC
  5A@ 250 VAC
  8A @ 30 VDC

## Protean<sup>™</sup> HT Radio Kit

Input Power	No. of Transmitters	Part No.
AC	1	700PR06HT
AC	2	700PR06DHT
DC	1	700PR06HT-DC
DC	2	700PR06DHT-DC