



- NOTES:
1. REEL SIZED TO STRETCH 100 FT ACTIVE + 7 FT FOR HOOK-UP = 107 FT OF 8AWG 4C TYPE W CABLE.
  2. SLIP RING: 75 AMP., 4 COND., 600V.

ITEM	MATERIAL NO. 2	DESCRIPTION	QTY.	UNIT
14	XA-08433	TERMINAL PS 34217 FOR 6 AWG	.33	PC
13	XA-43399	SPROCKET KIT 1.25 RATIO DUAL MOT 32/3600	1	PC
12	XA-43357	SPOOL ASSY 3200 X 5.1 X 11.9	1	PC
11	XA-RA-E04-PR	SLIP RING 1.5B 75A 4C 42IN LEADS	1	PC
10	XA-43376	MOTOR ASSY DUAL F SPRING	2	PC
9	XA-962150	MANUAL 3200/3600 POWERREEL	1	PC
8	XA-46967-75	JUMPER WIRE 6AWG 32/3600 REELS	1	PC
7	XA-43353-P	GUIDE RAIL ASSY 5.1 SPOOL 3200 YEL	1	PC
6	XA-43351	GUIDE ASSY 5.1IN SPOOL YEL	1	PC
5	XA-43413	FRAME ASSY DUAL MOT 3200/3600	1	PC
4	XA-04534-Y	ENCLOSURE 1.5B CR 9.25 LG YEL	1	PC
3	XA-553739	CRATE 3600 QUICK-CRATE	1	PC
2	XA-43381	CABLE KIT 0.875-1.00 3200/3600	1	PC
1	XA-33060	CABLE 8AWG 4C TYPE W	107	FT

STATUS: <b>RELEASED</b>		DESCRIPTION: <b>REEL PR 32A22F12DE04 S 100FT 8/4</b>	
ER NO. 65711	INTERPRET: GEOMETRIC TOLERANCING PER: ASME Y14.5-1994	PROPRIETARY AND CONFIDENTIAL	
ER DATE: 09/11/2015	UNLESS OTHERWISE SPECIFIED	This drawing and the information shown constitute trade secret and confidential property of Conductix-Tampier, Inc. It is subject to recall, and is loaned for use only in connection with the authorized manufacture or installation of Conductix-Tampier products, and on the condition that it will be treated as confidential and will not be disclosed, published or reproduced in whole or in part, or permitted to be viewed or used by any other party, without specific written permission. Receipt and use of the drawing and information constitutes acceptance and agreement to the above.	
ER ENGR: S JOHANEK	PRIMARY UNITS ARE IN INCH POUND SECONDS	10102 F Street Omaha, NE 68127 800-521-4888	
ER APPR: D SAMPSON	SECONDARY UNITS IN MILLIMETERS KILOGRAMS SECONDS	MATERIAL NO. 2: <b>XA-323080410021</b>	
DRAWN: S JOHANEK	TOLERANCES ARE AS FOLLOWS	REV <b>0</b>	
APPR: D SAMPSON	DECIMAL: .XX ± 0.1 IN (2.5 MM)	SIZE <b>B</b> SCALE: 1:10 WEIGHT(REF): 532.75 LB	
	X.XX ± 0.03 IN (0.8 MM)	MAT'L:	
	X.XXX ± 0.010 (0.25 MM)	SHEET 1 OF 1	
	ANG. ± 1°		
	FRAC. ± 1/16		
	THREAD CLASS: 2		
	ALL DIMENSIONS GREATER THAN 24.00 INCHES HAVE A TOLERANCE OF ± .063 IN UNLESS OTHERWISE SPECIFIED		